

DIVISION 06 - WOOD, PLASTIC, AND COMPOSITES

2006 Edition, Published January 1, 2006; Division Revision Date: January 1, 2006

06 00 00. WOOD, PLASTIC, AND COMPOSITES

06 00 03. GENERAL PROVISIONS

.1 USE OF INK MARKING PENS ON SURFACES of any kind of materials is prohibited. Experience has shown that such marks bleed through paint and other finishes.

06 05 73. WOOD TREATMENT

.1 PROTECTION AGAINST DECAY: Wood used in conjunction with roofing installations and wood which is installed in contact with concrete or masonry shall be pressure treated with an approved preservative to meet AWPS Standards. Other installations shall receive prime coats suitable for finishes specified as soon as installations are completed. Back prime where dampness or warping is anticipated. Wood preservatives containing arsenic such as CCA for exterior construction above ground on in ground contact or fresh water is prohibited.

06 10 00. ROUGH CARPENTRY

.1 WOOD FRAMING: Stud and furring strip spacing shall be 16 inches on center, maximum.

06 13 00. HEAVY TIMBER

.1 TIMBER TRUSSES: With the shop drawings, a complete design analysis of structural components shall be submitted. Data shall bear the seal and signature of a professional engineer, registered in Ohio, attesting that the design of trusses meets requirements of the Ohio Building Code (OBC) and design loadings.

06 17 00. SHOP-FABRICATED STRUCTURAL WOOD

.1 WOOD TRUSSES: Same as 06 13 00.1. above.

06 20 00. FINISH CARPENTRY

.1 MATERIALS AND FABRICATION: Conform to Architectural Woodwork Institute specifications for Custom quality work.

06 22 00. MILLWORK

.1 MATERIALS AND FABRICATION: Refer to the Architectural Woodwork Institute "Quality Standards", latest edition. Use "Custom Grade" for standard woodwork. Use "Premium Grade" for unique and special projects or features within a project.

06 40 00. ARCHITECTURAL WOODWORK

.1 CABINET WORK: Materials and fabrication shall conform to Architectural Woodwork Institute specifications for Premium quality work. Written certification is required from the fabricator that Architectural Woodwork materials, construction and installation comply with the specified standards.

END OF DIVISION 06 – WOOD AND PLASTIC